



Tech Info Library

Using Catalyst 2.0 with the Apple III and hard disk drives

Revised: 7/27/85
Security: Everyone

Using Catalyst 2.0 with the Apple III and hard disk drives

=====

To use Catalyst 2.0 with the Apple III and hard disk drives other than the ProFile, you need to change the driver configuration block of the .CATALYST driver as follows:

00	01	02	03	04	05	06	07	08	09	0A	0B	0C	0D	0E	0F	10	11
--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--
(See notes just below)						00	8F	97	8A	91	93	23	17	17	F6	00	B8

Notes:

00 - Slot number
01- Unit number
02 - Type
03 - Sub Type
04 - Low Byte, Manufacturer's ID
05 - High Byte, Manufacturer's ID

For a 10 megabyte ProFile, copy the information in bytes 00 through 05 from the existing Catalyst hard disk driver configuration block (DCB) of the Catalyst driver that you are using. For a 10 MB Profile, the DCB should look like this:

	00	01	02	03	04	05	06	07	08	09	0A	0B	0C	0D	0E	0F	10	11
	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--
slot	00	01	01	23	00	00	8F	97	8A	91	93	23	17	17	F6	00	B8	

For a 5 MB Profile, the DCB should look like this:

	00	01	02	03	04	05	06	07	08	09	0A	0B	0C	0D	0E	0F	10	11
	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--
slot	00	D1	01	23	00	00	8F	97	8A	DD	93	23	E8	17	F6	3B	C3	

Apple Technical Communications

Tech Info Library Article Number:264