



# Tech Info Library

## Apple III: Cables for Various Printers (4 of 4)

Revised: 11/19/86  
Security: Everyone

Apple III: Cables for Various Printers (4 of 4)

=====

Apple III Drivers Aid Cable "K"

Device Manufacturer and Model:

IDS 125  
IDS 225  
IDS 440  
IDS 445  
IDS 460  
IDS 560

Pin-to-Pin Connections

Apple III (Male) IDS (usually Female)

2 o-----o 3  
6 o-----o 20  
7 o-----o 7

Note: For proper operation when using the Apple III Super Serial Card (Apple P/N A2B0044) in an Apple III make sure that switch SW 2-6 (on the card) is in the "ON" position and that the jumper block (also on the card) is in the "TERMINAL" Position.

Apple III Drivers Aid Cable "L"

Device Manufacturer and Model:

Axiom EX-801  
Axiom EX-820  
Comprint 912  
DEC LA34  
Teletype 43

Pin-to-Pin Connections:

Apple III (Male) Printer (usually Female)

1 o-----o 1

2 o-----o 3  
6 o-----o 20  
7 o-----o 7

Note: For proper operation when using the Apple III Super Serial Card (Apple P/N A2B0044) in an Apple III make sure that switch SW 2-6 (on the card) is in the "ON" position and that the jumper block (also on the card) is in the "TERMINAL" Position.

Apple Technical Communications

Tech Info Library Article Number:295