

Tech Info Library

BASIC: APPEND fix (2 of 2)

Revised: 11/15/84 Security: Everyone

BASIC: APPEND fix (2 of 2)

For those who do not feel comfortable with the above machine language, use the following procedure to make new slave diskettes with the corrected DOS:

- 1. Boot the system with an initialized diskette. This loads the old DOS into your Apple.
- 2. Type in the BASIC program below and RUN it. This will change the old DOS in memory to the corrected DOS.
- 3. SAVE this program just in case you made a typo.
- 4. Without rebooting the system, run the 4 test programs above to see if APPEND works correctly.
- 5. Type NEW; insert a blank diskette, and type INIT HELLO. This creates a diskette with the corrected DOS.
- 6. Use this new diskette whenever initializing other diskettes; the corrected DOS will be carried over.

Use this BASIC program in step 2 above:

- 10 POKE -18813,76 : POKE -18812,179 : POKE -18811,182
- 20 FOR I = -18765 TO -18738
- 30 READ A: POKE I, A: NEXT
- 40 FOR I = -17788 TO -17773
- 50 POKE I,0: NEXT
- 60 PRINT "DONE..."
- 75 END
- 80 DATA 173,189,181,141,230,181,141,234,181,173,190,181,141,231, 181,141,235,181,141,228,181,186,142,155,179,76,127,179

Apple Technical Communications

Tech Info Library Article Number: 331