



Tech Info Library

Apple III Pascal: Reading special keyboard characters (2 of 2)

Revised: 11/15/84
Security: Everyone

Apple III Pascal: Reading special keyboard characters (2 of 2)

```
=====

procedure KEY_NAME;
var Its_There: integer;
begin
  Key:= ' '; {Initialize as one character}
  if (A > 127) then A:= A - 128; {Open-Apple
                                flagged elsewhere}
  if (A < 33) then begin
    Its_There:= pos ('Special', Mod_Key);
    if (Its_There > 0) then begin
      case (A) of
        8: Key:= 'LeftArrow';
        9: Key:= 'Tab';
        10: Key:= 'DownArrow';
        11: Key:= 'UpArrow';
        13: Key:= 'Enter';
        21: Key:= 'RightArrow';
        27: Key:= 'Escape';
        32: Key:= 'Space'
      end;
      delete (Mod_Key, 1, 7); {Delete 'Special'}
    end
  else begin
    Key [1]:= chr (A + 64); {Convert to regular character}
    if (A = 13) then begin
      Its_There:= pos ('Control', Mod_Key);
      if (Its_There = 0) then Key:= 'Return'
    end
  end
  end
  else begin {Printing characters}
    Key [1]:= chr (A);
    if (A = 127) then Key:= 'Delete'
  end
end; {Key_Name}

begin
```

```
write (chr (28)); {Clear viewport}
KBD_MODE (128); {Request 2-byte keyboard operation}
repeat
  write ('Enter key combination: ');
  READ_TWO;
  MODIFIER; {Interpret Byte_B}
  KEY_NAME; {Interpret Byte_A}
  writeln (Mod_Key, Key);
until (Key = 'Escape');
KBD_MODE (0) {Restore 1-byte keyboard operation}
end. {Two_Bytes}
```

Apple Technical Communications

Tech Info Library Article Number:339