



# Tech Info Library

## Super Serial Card: Cable for IDS 125,225,440,445,460,560 (11/96)

Revised: 11/21/96  
Security: Everyone

Super Serial Card: Cable for IDS 125,225,440,445,460,560 (11/96)

Article Created: 04 December 1984  
Article Reviewed/Updated: 21 November 1996

TOPIC -----

Listed below are the cable pinouts for connecting the Super Serial card to a IDS 125, 225, 440, 445, 460, or 560 printer.

DISCUSSION -----

| Super Serial Card (SSC) | Pin           | Cable   | Pin    | Printer Connector |
|-------------------------|---------------|---------|--------|-------------------|
| Frame Ground .....      | (FG)..... 1   |         |        |                   |
| Transmit Data           | (Tx) ..... 2  | <-----> | 3..... | (Rx)              |
| Receive Data            | (Rx) ..... 3  |         |        |                   |
| Request to send         | (RTS) .... 4  |         |        |                   |
| Clear To Send           | (CTS) .... 5  |         |        |                   |
| Data Set Ready          | (DSR) .... 6  | <-----> | 20.... | (DTR)             |
| Signal Ground .....     | (SG)..... 7   | <-----> | 7..... | (SG)              |
| Data Carrier Detect     | (DCD) .... 8  |         |        |                   |
| Secondary Clear To Send | (SCTS) ... 19 |         |        |                   |
| Data Terminal Ready     | (DTR) .... 20 |         |        |                   |

Article Change History:  
21 Nov 1996 - Reviewed for technical accuracy, revised formatting.

Copyright 1984-96, Apple Computer, Inc.

Tech Info Library Article Number:938