

Tech Info Library

ImageWriter: Interface Specifications (8/94)

Revised: 10/18/94 Security: Everyone

ImageWriter: Interface Specifications (8/94)

Article Reviewed/Updated: 31 August 1994

TOPIC -----

This article gives the interface specifications for the Apple Imagewriter printer.

NOTE: This product is discontinued and is no longer available.

DISCUSSION -----

1. Data Input Form:

7-bit or 8-bit serial: 1 start bit

7 or 8 data bits

1 stop bit (no parity bit)

2. Data Input Codes:

Characters: ASCII, 8- or 7- bit

Graphics: 8-bit binary

- 3. Transmission Speed: 300, 1200, 2400, or 9600 baud
- 4. Input Buffer Size: 1K bytes
- 5. Printer Connector: DB-25 male, or equivalent
- 6. Mating Connector: DB-25S female, or equivalent
- 7. Printer Pin Out

Pin	No.	Symbol	Description	Direction
	1	FG	Frame Ground	
	2	SD	Send Data	Output
	3	RD	Receive Data	Input
	4	RTS	Request to Send	Output

..TIL01234-ImageWriter-Interface_Specifications_8-94.pdf

- 7 SG Signal Ground
- 14 FAULT FaultOutput
- 20 DTR Data Terminal Ready Output
- 8. Signal Description
- 9. Frame Ground: Grounding line for circuit protection.
- 10. Send Data: Serial dot transmission line to the computer from the printer. False when no data is being sent; true when data is being sent.
- 11. Receive Data: Serial data transmission line to the printer from the computer. False when no data is being sent; true when data is being sent.
- 12. Request to Send: Output segnal from the printer; true when the printer is turned on.
- 13. Fault: Output signal from the printer. False when the printer is deselected; true when selected.
- 14. Data Terminal Ready: Output segnal from the printer. True whan the printer is on and able to receive data; false when unable to receive data.
- 15. Signal Levels:
 - RD: Maximum +15 Volts, minimum +5 Volts.
 - SD, RTS, DTR, and FAULT signal levels: Normal +7 Volts.
- 16. Protocol

The printer is capable of two types of data protocol: XON/XOFF or Data Terminal Ready (DTR). The DTR protocol uses the DTR signal to indicate the printer state. The XON/XOFF protocol uses the serial ASCII codes for XON and XOFF.

Article Change History:

31 Aug 1994 - Removed "Discontinued" from title. Updated and reviewed.

Support Information Services

Copyright 1985-94, Apple Computer, Inc.

Tech Info Library Article Number:1234