



# Tech Info Library

## Macintosh 128K & 512K: Specifications (Discontinued)

Revised: 9/26/95  
Security: Everyone

Macintosh 128K & 512K: Specifications (Discontinued)

=====

Date Created: 16 June 1985  
Article Reviewed/Updated: 26 September 1995

TOPIC -----

This article provides specifications for the Macintosh 128K and 512K.

DISCUSSION -----

### MICROPROCESSOR

- Motorola MC68000, 32-bit architecture, 8 (7.8336) MHz clock speed

### MEMORY

- 128K or 512K of RAM (Random Access Memory)
- 64K of ROM (Read Only Memory)

### DISK DRIVE

- One built-in 400K disk drive. Optional external 400K disk drive.

### SCREEN

- Built-in 9-inch diagonal, 512 by 342-pixel high-resolution bit-mapped monochrome display

### INTERFACES

- Mouse port, DB-9 connector
- One eight-bit keyboard bus, 300 baud, RJ11 connector for Macintosh keyboard
- Two RS-232/RS-422 serial ports, 230.4K baud maximum (up to 0.920 Mbit per second if clocked externally), DB-9 connector
- External Disk Drive interface
- Sound port for external audio amplifier or headphones

### CLOCK/CALENDAR

- CMOS custom chip with 4.5 volt battery backup (Eveready No. 523 or equivalent)

#### ELECTRICAL REQUIREMENTS

- Line voltage: 105 to 125 volts AC
- Line frequency: 50 to 60 hertz
- Maximum power: 60 watts

#### ENVIRONMENTAL REQUIREMENTS

- Operating temperature: 50 to 104 degrees F (10 to 40 C)
- Storage temperature: -40 to 122 degrees F (-40 to 50 C)
- Relative humidity: 5% to 90% relative humidity
- Altitude: 15,000 feet (4615 meters)

#### SIZE AND WEIGHT

- Height: 13.5 inches (34.6 cm)
- Width: 9.7 inches (24.6 cm)
- Depth: 10.9 inches (27.6 cm)
- Weight: 16 lb. 8 oz. (7.5. kg)

#### Article Change History:

26 Sep 1995 - Reviewed for technical accuracy.

Support Information Services

Copyright 1985, 1986 Apple Computer, Inc.

Tech Info Library Article Number:1285