



# Tech Info Library

## ImageWriter II: Pinouts & Switch Settings

Revised: 9/27/85  
Security: Everyone

ImageWriter II: Pinouts & Switch Settings

Switch settings:

```

                                     Switch SW1
                                     1  2  3  4  5  6  7  8
Character Sets:
  English (US)      Off Off Off
  Italian           On  Off Off
  Danish            Off On  Off
  English (UK)      On  On  Off
  German            Off Off On
  Swedish           On  Off On
  French            Off On  On
  Spanish           On  On  On
Page length:
  66 lines (11 inch)      Off
  72 line (12 inch)      On
Perforation skip
  inactive              Off
  active                On
Character Pitch:
  160 DPI (Proportional) Off Off
  12 CPI                On  Off
  17 CPI                Off On
  10 CPI                On  On
Auto linefeed after CR:
  Enable                On
  Disable              Off
                                     1  2  3  4  5  6  7  8
                                     Switch SW2
                                     1  2  3  4
Baud Rate:
  300      Off Off
  1200     On  Off
  2400     Off On
```

9600	On	On		
Data Protocol:				
XON/XOF			On	
DTR			Off	
Option card				
Disabled				Off
(No option card)				
Enabled			On	
	1	2	3	4

KEY: Off = Open; On = Closed

WARNING: DO NOT CHANGE DIP switches SW 2-5 and SW 2-6: they control the timing of the firing of the hammer and are therefore preset at the factory.

Pinouts:

Pin No.	Symbol	Description	Direction
1	DTR	Data Terminal Ready	Output
2	DSR	Data Set Ready	Input
3	TxD-	Transmit Data-	Output
4	SG	Signal Ground	
5	RxD-	Receive Data-	Input
6	TxD+	Balanced Transmit+	Output
7	NC	No Connection	
8	RxD+	Balanced Receive+	Input
Shield	PG	Protective Ground	

Apple Technical Communications

Tech Info Library Article Number:1301