

MICROCOM MACMODEM 2400: Using it With All Apples

Revised: 8/3/93 Security: Everyone

MICROCOM MACMODEM 2400: Using it With All Apples

Article Created: 21 October 1985

- Modem type: AT&T 103/212A series; 2400, 1200, 300, 0-110 bps.
- Instruction set used: Hayes compatible Macmodem software provides all modem control functions.
- Hardware configuration: Six LED indicators on front panel give modem and data status. Modem plugs into Macintosh Communications port, and terminal software provides auto-dial number storage. Modem runs off of 17VAC plug in power supply. Built-in speaker is used to monitor operation and diagnostics.
- Software configuration: Computer controlled intelligent modem with number storage, auto-dial and auto-answer functions.
- Interface type: Macintosh DB-9 connector, full duplex operation.

Modem interface packages, by computer:

- Apple IIe: Not useable.
- Apple IIc: Not useable.
- Apple III: Not useable.
- Macintosh: MICROCOM MACMODEM terminal software, with the modem providing the cable for hardware connection.

• Macintosh XL:

MICROCOM MACMODEM terminal software, with a DB-9 to DB-25 adapter needed to connect the modem cable to the Macintosh XL port for hardware connection.

Copyright 1985, Apple Computer, Inc.

Tech Info Library Article Number:1335