



Tech Info Library

LaserWriter II: Specifications (Discontinued 2/88)

Revised: 9/20/93
Security: Everyone

LaserWriter II: Specifications (Discontinued 2/88)

=====

This article last reviewed: 27 April 1988

Here are the technical specifications for a LaserWriter II:

Printing Method

Electrophotography (single-component dry toner)

Printing Speed

Cassette Feed: 8 prints/ minute (other than legal size)
7 prints/ minute (legal size)

Optical System

Laser: semiconductor laser
Scanning System: rotating 6-faced prism mirror

Paper

Cassette Feed 16 to 24 lbs. single sheet photocopy bond
Manual Feed 16 to 36 lbs. letterhead and colored stock
Standard Weight transparency material
Envelopes and labels

Cassettes/Capacity/Sizes

Auto 200 sheets: US Letter, Legal, A4, B5
Manual Single sheets: US Letter, Legal, A4, B5
Envelope 15 envelopes

Print delivery/Capacity

Face-down 100 sheets
Face-up 20 sheets

(NOTE: Always open the face-up tray when printing stock above 21 lbs., or when printing envelopes or transparencies.)

Duty Cycle (month) No limit

Minimum life expectancy: 300,000 pages

Service Interval: 100,000 pages

Pages per Toner: 4000 pages

Noise Level

Printing Under 60 dB(A)

Standby Under 50 dB(A)

Dimensions W 20.2" x D 18.7" x H 8.7"

Weight 46 lbs.

Power Consumption

Standby Average 170W

Operating Maximum 900W (115V)

780W (220V)

880W (240V)

Line Voltage requirements Voltage (V) 10% Frequency (Hz)

US/Japan 100/115 50/60

Europe/Australia 220/240 50

Copyright 1988, 1992, Apple Computer, Inc.

Tech Info Library Article Number:1944