



Tech Info Library

Macintosh 512Ke: Specifications (Discontinued) (8/94)

Revised: 9/2/94
Security: Everyone

Macintosh 512Ke: Specifications (Discontinued) (8/94)

Article Created: 18 July 1986
Article Reviewed/Updated: 2 September 1994

TOPIC -----

This article gives the technical specifications for the Macintosh 512K enhanced computer.

DISCUSSION -----

MICROPROCESSOR

- Motorola MC68000, 32-bit architecture, 8 (7.8336) MHz clock speed

MEMORY

- 512K of RAM (Random Access Memory)
- 128K of ROM (Read Only Memory)

DISK DRIVE

- One built-in 800K disk drive. (Optional external 400K or 800K disk drive.)

SCREEN

- Built-in 9-inch diagonal, 512 by 342-pixel high-resolution bit-mapped monochrome display

INTERFACES

- Mouse port, DB-9 connector
- One eight-bit keyboard bus, 300 baud, RJ11 connector for Macintosh keyboard
- Two RS-232/RS-422 serial ports, 230.4K baud maximum (up to 0.920 Mbit per second if clocked externally), DB-9 connectors
- External Disk Drive interface (400K or 800K disk drives)
- Sound port for external audio amplifier or headphones

CLOCK/CALENDAR

- CMOS custom chip with 4.5 volt battery backup (Eveready No. 523 or

equivalent)

ELECTRICAL REQUIREMENTS

- Line voltage: 105 to 125 volts AC
- Line frequency: 50 to 60 hertz
- Maximum power: 60 watts

ENVIRONMENTAL REQUIREMENTS

- Operating temperature: 50 to 104 degrees F (10 to 40 C)
- Storage temperature: -40 to 122 degrees F (-40 to 50 C)
- Relative humidity: 5% to 90% relative humidity
- Altitude: 15,000 feet (4615 meters)

SIZE AND WEIGHT

- Height: 13.5 inches (34.6 cm)
- Width: 9.7 inches (24.6 cm)
- Depth: 10.9 inches (27.6 cm)
- Weight: 16 lb. 8 oz. (7.5. kg)

Article Change History:

2 Sep 1994 - Corrected the article title.

Support Information Services

Copyright 1986-94, Apple Computer, Inc.

Tech Info Library Article Number:1970