



# Tech Info Library

## A/UX sendmail: How to Resolve Address Path and Rebuild (9/94)

Revised: 9/14/94  
Security: Everyone

A/UX sendmail: How to Resolve Address Path and Rebuild (9/94)

=====

Article Created: 31 May 1988

TOPIC -----

A/UX sendmail: How to Resolve Address Path and Rebuild

DISCUSSION -----

The "/usr/lib/sendmail.cf" file in A/UX is configured with four rules for resolving the address path:

1. For the root@host type of mail syntax, is host in the /usr/lib/uucp/L.sys file?
  - If yes, then path is via "uucp".
  - If no, then path is via "tcp".
2. For the root@host.uucp type of mail syntax, is host in the /usr/lib/uucp/L.sys file?
  - If yes, then path is via "uucp".
  - If no, then path is via "uumail".

(Note that "uumail" is a foreign mailer not yet included in A/UX.)

3. For the root@host.<any domain except uucp> type of mail syntax:

path is via "tcp" (it doesn't matter whether the host is in the /usr/lib/uucp/L.sys or /etc/hosts file).

4. For the host!root type of mail syntax:

path is via "uucp" (it doesn't matter whether the host is in the /usr/lib/uucp/L.sys or /etc/hosts file).

To rebuild a "sendmail.fc" (sendmail frozen configuration file) that might be corrupted or out of date, run the following command:

```
/usr/lib/sendmail -bz
```

Whenever modifying the "sendmail.cf", you should run this command to update the "sendmail.fc" file, because the sendmail daemon reads it to resolve the destination address.

Article Change History:

13 Sep 1994 - Reviewed.

31 Aug 1992 - Reviewed.

Support Information Services

Copyright 1988, 1994 Apple Computer, Inc.

Tech Info Library Article Number:2975