

# **Macintosh Portable: Internal 40SC Hard Disk**

Revised: 7/27/92 Security: Everyone

Macintosh Portable: Internal 40SC Hard Disk

\_\_\_\_\_\_

Article Created: 13 September 1989 Article Last Reviewed: 27 July 1992

Article Last Updated:

TOPIC -----

This article gives the a technical description of the Macintosh Portable Internal 40SC Hard Disk.

DISCUSSION -----

The Macintosh Portable Internal 40SC Hard Disk provides fast, reliable access to high-performance storage and large-capacity applications. One-inch high, weighing 1.1 pounds, the Macintosh Internal Hard Disk 40SC has been designed especially for use with the Macintosh Portable. It draws little power from system batteries and virtually eliminates disk swapping, because it can accomodate multiple applications, complex documents, and large databases in one convenient location.

#### SPECIFICATIONS

Mechanism Size : 3.5 Inches

#### CAPACITY 40MB

- Data Capacity: 40MB Formatted

Data surfaces: 2Heads/Surfaces: 1Block Size: 512 bytesTotal disk blocks: 82,080

- Blocks/Tracks: 40

## CHARACTERISTICS

- Average Seek Time : 25 milliseconds

Rotational Speed: 3,557 rpmStartup Time: 20 seconds

## ..TIL04485-Macintosh\_Portable-Internal\_40SC\_Hard\_Disk\_(TA40409).pdf

- Spin-down Time: 10 seconds
- Automatically retracks to the inner stop (non-data area) upon power down to protect data area during travel and startup.

### ENVIRONMENTAL

- Operating Temperature: 50 degrees F to 104 degrees F (10 degrees C to 40 degreesC)
- Non-Operating Temperature: 32 degrees F to 122 degrees F (0 degrees C to 50 degrees C)
- Humidity: 20% to 80% relative humidity non condensing

Interface : internal 34-pin connector

Copyright 1989 Apple Computer, Inc.

Tech Info Library Article Number:4485