



# Tech Info Library

## A/UX: How to Make an NFS Daemon Run (9/94)

Revised: 9/7/94  
Security: Everyone

A/UX: How to Make an NFS Daemon Run (9/94)

=====

Article Created: 15 October 1990  
Article Reviewed/Updated: 6 September 1994

TOPIC -----

My NFS daemon isn't running. Why not?

DISCUSSION -----

Was the nfs daemon started in /etc/inittab? If not, follow these steps:

1) Log on as "root".

2) Edit the file /etc/inittab

3) Change the line

```
nfs3:2:off:/etc/nfsd 4      # set to "wait" for NFS server
```

to:

```
nfs3:2:wait:/etc/nfsd 4     # set to "wait" for NFS server
```

4) Enter the line: telinit q

5) Enter the line: ps -ef | grep nfsd (or, ps-a | grep nfsd in the C shell)

The output should resemble the following:

```
root  93 1  0 10:00:34?    0:00 /etc/nfsd 4
root  94 1  0 10:00:35?    0:00 /etc/nfsd 4
root  95 1  0 10:00:35?    0:00 /etc/nfsd 4
root  96 1  0 10:00:35?    0:00 /etc/nfsd 4
```

Note that the numbers in the columns may differ on your system.

Article Change History:

06 Sep 1994 - Reviewed.

31 Aug 1992 - REVIEWED for technical accuracy.

Support Information Services

Copyright 1990-94 Apple Computer, Inc.

Tech Info Library Article Number:6312