



# Tech Info Library

## LaserWriter IISC: Specifications (Discontinued)

Revised: 9/21/93  
Security: Everyone

LaserWriter IISC: Specifications (Discontinued)

=====

Article Created: 15 March 1991

### Marking Engine

-----

Canon LBP-SX laser xerographic

### Processor

-----

Motorola 68000 (7.45 MHz clock speed)

### Memory

-----

16K ROM; 1MB RAM

### Interfaces

-----

SCSI and Apple Desktop Bus (for future expansion) ports

### Macintosh Fonts (on Disk)

-----

Times, Helvetica, Courier, and Symbol typefaces in 9-, 10-, 12-, 14-, 18-, and 24-point sizes. (For best results, these fonts should be installed in the System file of your Macintosh computer from the disks shipped with the LaserWriter IISC)

### Speed

-----

8 pages per minute maximum throughput (actual speed depends on images printed)

### Print Quality

-----

All text and graphics printed at 300 by 300 dots per inch, full page

### Print Materials

-----

# ..TIL06970-LaserWriter\_IISC-Specifications\_Discontinued.pdf

Letter, legal, A4, and B5 sizes using 16- to 20-lb. single-sheet photocopy bond, 8- to 34-lb. letterhead and colored stock, or transparency overhead film. Envelopes, labels, and paper (up to 36-lb.) supported via manual feed. Envelopes also supported via optional envelope tray.

## Print Capacities

- Paper cassettes hold 200 sheets of 20-lb. paper.
- Envelope cassette holds 15 envelopes.

## Printable Surface

- letter size: 8.0 by 10.5 in.
- legal: 8.0 by 13.0 in.
- A4: 7.41 by 10.86 in.
- B5: 7.69 by 10.16 in.

(Actual printable area may vary depending on application.)

## Size and Weight

- Height: 8.6 in. (21.8 cm)
- Width: 20 in. (50.8 cm)
- Width: With letter tray attached, 26.4 in. (67.1 cm)
- Depth: 18.5 in. (47 cm)
- Weight: 45 lb. (20.25 kg)

## Operating Environment

- Temperature: 50 to 90 degrees F (10 to 32 C)
- Humidity: 20% to 80%

## Power Requirements

90 to 126 VAC, 50 to 60 Hz

Copyright 1991, Apple Computer, Inc.

Tech Info Library Article Number:6970