



Tech Info Library

Macintosh LC: Connecting to VGA Monitors

Revised: 7/23/92
Security: Everyone

Macintosh LC: Connecting to VGA Monitors

Article Created: 5 March 1991
Article Last Reviewed: 23 July 1992
Article Last Updated: 23 July 1992

TOPIC -----

Does the Macintosh LC support VGA monitors? What are the pinouts for connecting a VGA monitor to a Macintosh LC?

DISCUSSION -----

The Macintosh LC supports some VGA monitors. However, there are many different modes/types of VGA timing. The following specifications show the VGA timing characteristics supported by the Macintosh LC.

Dot clock	= 25.175 MHz
Dot	= 39.722 nsec
Full line	= 31.778 usec
Line rate	= 31.469 kHz
Full frame	= 16.68 msec
Frame rate	= 59.94 Hz

Here are the pinouts for connecting a VGA monitor to a Macintosh LC:

Macintosh LC		VGA Connector
DB-15		
-----		-----
2	----- Red Video	1
1	----- Red Ground	6
9	----- Blue Video	3
13	----- Blue Ground	8
5	----- Green Video	2
6	----- Green Ground	7
15	----- Hsync	13

```
12 ----- Vsync ----- 14
14 ----- Sync Ground ----- 10
10 -----|
7 -----| Connect 7 and 10 so the sense pin ID will equal VGA
```

A few issues to keep in mind:

- VGA monitors may vary depending on the vendor. Check with the vendor about Macintosh LC compatibility before buying.
- Vendors have different image quality specifications. There may significant differences between Apple monitors and VGA monitors. Do a side-by-side comparison of a VGA monitor with an Apple monitor before buying.
- Third party cable vendors should have cables available for purchase soon.
- When a VGA monitor is connected as described in the pinout above, the resolution is 640 x 480. The bit-depth supported depends on the amount of VRAM installed. For example, if the Macintosh LC 256K VRAM SIMM is installed, 4-bit color (16 colors) is supported. If the Macintosh LC 512K VRAM SIMM is installed, 8-bit (256 colors) is supported.

Copyright 1991, 1992 Apple Computer, Inc.

Tech Info Library Article Number:7088