



# Tech Info Library

## Macintosh IIfx: 4MB SIMM Configuration (11/94)

Revised: 11/8/94  
Security: Everyone

Macintosh IIfx: 4MB SIMM Configuration (11/94)

Article Created: 25 July 1991  
Article Reviewed/Updated: 08 November 1994

TOPIC -----

I have a Macintosh IIfx with 4MB of RAM and a Macintosh Display Card 8•24 GC installed. When I add the 8•24 GC CDEV to the System Folder and try to start up the system, it hangs at the "Welcome to Macintosh" message. When I remove the 8•24 GC CDEV from the System Folder, the system starts up and operates normally. (This does not happen with a Macintosh IIfx with 8MB of RAM installed.)

DISCUSSION -----

This problem is peculiar to the Macintosh IIfx with 4MB of RAM installed. Apple states that, when using only 4MB of RAM in the Macintosh IIfx, the SIMMs MUST BE installed in bank A. Although the Macintosh IIfx may work normally in some configurations with the SIMMs installed in bank B; in others, it doesn't.

To eliminate the problems you are experiencing with the Macintosh IIfx, make sure the RAM SIMMs are in bank A.

Article Change History:  
08 Nov 1994 - Reviewed for technical accuracy.

Support Information Services

Copyright 1991-94, Apple Computer, Inc.

Tech Info Library Article Number:7931