

# Tech Info Library

### Macintosh 21 Color Display: Specifications (Discontinued 3/94)

Revised: 3/14/94 Security: Everyone

Macintosh 21" Color Display: Specifications (Discontinued 3/94)

\_\_\_\_\_\_

Article Created: 1 October 1991

Article Reviewed/Updated: 14 March 1994

TOPIC -----

This article gives the technical specifications for the Macintosh 21-inch Color Display, which Apple discontinued on 14 March 1994, replacing it with the Apple Multiple Scan 20 Display.

DISCUSSION -----

#### System Requirements

\_\_\_\_\_

- Macintosh personal computer equipped with an appropriate video card
- Video cable (supplied with the display)

#### Optical Features

\_\_\_\_\_

- 20-inch diagonal viewable with in-line gun
- 90 degree deflection angle
- Black matrix-type dot screen
- Phosphor type P22 (aluminized)
- Flat, square faceplate with gray filter glass, 50% nominal light transmission
- Shadow mask

#### Screen Resolution

-----

- 1152 horizontal pixels by 870 vertical lines; 79 dots per inch (dpi)
- .26 mm horizontal by .29 mm vertical dot pitch

#### Input Signals

-----

- Red, green, and blue video signals; TTL separate sync

User Controls

## ..TIL08921-Macintosh\_21\_Color\_Display-Specifications\_Discontinued\_3-94.pdf

- Back panel
  - Power switch (above power cord)
  - Manual degauss (above security lock)
- Front panel
  - Brightness, with detent (right)
  - Contrast (left of brightness control)

#### Scanning and Refresh Rates

\_\_\_\_\_

- Horizontal scan rate: 68.7 kilohertz
- Vertical refresh rate: 75 hertz

#### Rise and Fall Time

\_\_\_\_\_

- Five nanoseconds, maximum

#### Active Video Display Area

\_\_\_\_\_

- 14.6 inches horizontal by 11.0 inches vertical (371 mm horizontal by 280 mm vertical); remainder of display area is used for border.

#### Electrical Requirements

-----

- Voltage: 85 to 135 volts AC or 170 to 270 volts AC

Frequency: 47 to 63 hertzPower: 165 watts maximum

#### Fuse Protection

\_\_\_\_\_

- Internal power line fuse protection; the display fuse should be replaced with a fuse of the same type by a qualified service technician.

#### Environmental Requirements

-----

- Operating temperature: 50 to 95 degrees F (10 to 35 degrees C)
- Operating humidity: 95% maximum, noncondensing
- Maximum altitude: 10,000 feet (3,048 m)

#### Size and Weight

-----

- Height: 18.5 inches (47.0 cm) - Width: 19.6 inches (49.8 cm) - Depth: 20.9 inches (53.0 cm) - Weight: 79.6 lb. (36.2 kg)
- Safety Agency Approvals

-----

- Emissions: FCC (class A), VDE (class A), FTZ, CISPR, Swedish MPR magnetic (VLF and ELF)
- Safety: UL, CSA, FDA/DHHS, Scandinavian EMKOs, PTB

#### Article Change History:

# $.. TIL 08921-Macintosh\_21\_Color\_Display-Specifications\_Discontinued\_3-94.pdf$

14 March 1994 - Added discontinuation information.

Copyright 1991-94, Apple Computer, Inc.

Tech Info Library Article Number:8921