

## Macintosh Duo Dock & Duo MiniDock: Specifications 1/96

Revised: Security:	
	Dock & Duo MiniDock: Specifications 1/96
Article Created: 19 October 1992 Article Reviewed/Updated: 3 January 1996	
TOPIC	
This article provides the technical specifications for the Macintosh Duo Dock and Macintosh Duo MiniDock.	
DISCUSSION	
MACINTOSH DUO DOCK TECHNICAL SPECIFICATIONS	

### Coprocessor

-----

• Optional 68882 math coprocessor

### Disk Storage

-----

- One internal 1.4MB Apple SuperDrive
- Bay for optional 1-in. high 3.5-in. SCSI hard disk drive (many capacities available)

### Video Display

\_\_\_\_\_\_

- Built-in video support for most Apple displays, up to and including the Macintosh 16" Color Display
- Supports some VGA and SVGA monitors with adapter cable

### Video RAM

-----

• 512K (256 colors or shades of gray), expandable to 1MB (32,000 colors) with optional 512K VRAM SIMM

• Provides enhanced video performance when optional 512K VRAM is installed

### Interfaces

\_\_\_\_\_

- One Apple Desktop Bus (ADB) port, supporting a keyboard, mouse, and other input devices
- One video port
- Two internal NuBus expansion slots for cards that provide Ethernet, Token Ring, additional video, or other capabilities
- Two RS-422 serial ports for printers, modems, and other serial devices
- Pass-through port for the optional modem in Macintosh PowerBook Duo notebook computer (RJ-11 or Mini-DIN-8)
- One HDI-30 SCSI port for external hard disks, scanners, CD-ROM drives, and other devices
- One sound-in port for monaural sound input
- One sound output port for external audio amplifier

### Security

-----

- Key lock prevents removal of the Macintosh PowerBook Duo from the Macintosh Duo Dock
- Slot for cable to secure the Macintosh Duo Dock to a desk

### Electrical Requirements

-----

- Line voltage: 85 to 270 V
- Frequency: 47 to 63 Hz

### Environmental Requirements

-----

- Operating temperature: 50° F to 104° F (10° C to 40° C)
- Storage temperature: -40° F to 116° F (-40° C to 47° C)
- Relative humidity: 20% to 95% noncondensing
- Altitude: 0 to 15,000 ft. (0 to 4722 m)

### Size and Weight

\_\_\_\_\_

- Height: 4.75 in. (12.1 cm)
- Width: 12.25 in. (31.1 cm)

- Depth: 16.25 in. (41.3 cm)
- Weight: 13.1 lb. (5.95 kg)
   (weight will be greater with internal hard disk)

#### MACINTOSH DUO MINIDOCK TECHNICAL SPECIFICATIONS

\_\_\_\_\_\_

### Video Display

\_\_\_\_\_

- Built-in video support for most Apple displays, up to and including the Macintosh 16" Color Display
- Supports some VGA and SVGA monitors with adapter

### Video RAM

-----

• 512K (256 colors or shades of gray)

### Interfaces

------

- One Apple Desktop Bus (ADB) port, supporting a keyboard, mouse, and other devices
- One video port
- Two RS-422 serial ports for printers, modems, and other serial devices
- Pass-through port to support the optional Macintosh PowerBook Express Modem in Macintosh PowerBook Duo notebook computer (RJ-11 or Mini-DIN-8)
- One HDI-30 SCSI port for external hard disks, scanners, CD-ROM drives, and other devices
- One HDI-20 port for the external 1.4MB floppy disk drive (MS-DOS compatible)
- One sound-in port for monaural sound input
- One sound output port for external audio amplifier

### Security

-----

• Slot for security cable

### Electrical requirements

\_\_\_\_\_\_

• Line voltage: 85 to 270 V

• Frequency: 47 to 63 Hz

Environmental requirements

```
• Operating temperature: 50° F to 104° F (10° C to 40° C)
• Storage temperature: -40^{\circ} F to 116^{\circ} F (-40^{\circ} C to 47^{\circ} C)
• Relative humidity: 20% to 95% noncondensing
• Altitude: 0 to 15,000 ft. (0 to 4722 m)
Size and weight
• Height: 2.1 in. (5.3 cm)
• Width: 10.6 in. (26.9 cm)
• Depth: 3.2 in. (8.1 cm)
• Weight: 1.24 lb. (.56 kg)
ORDERING INFORMATION
______
Macintosh Duo Dock ** Order No. M4179LL/A
_____
• Macintosh Duo Dock with internal 1.4MB Apple SuperDrive
• Mouse and microphone
• Power cable
• Security keys
• Complete setup, learning, and reference documentation
• Limited warranty statement
Macintosh Duo MiniDock ** Order No. M4181LL/A
_____
• Macintosh Duo MiniDock
• Complete setup, learning, and reference documentation (U.S., Japan)
· Limited warranty statement
```

Macintosh PowerBook Duo Floppy Adapter\* Order No. M4180LL/A

- Macintosh PowerBook Duo Floppy Adapter
- Plastic case for storage and travel

• Limited warranty statement

# Other Products

Macintosh VRAM Expansion Kit Order No. M1311LL/A

Macintosh Math Coprocessor Order No. M6775LL/A

Apple Ethernet NB Card Order No. M0417LL/A

Apple HDI-30 SCSI Disk Adapter Order No. M2539LL/A

Apple HDI-30 SCSI System Cable Order No. M2538LL/A

\*\* These devices have not been approved by the Federal Communications Commission. These devices are not, and may not be, offered for sale or lease, or sold or leased, until approval of the FCC has been obtained.

Support Information Services

Copyright 1992-96, Apple Computer, Inc.

Tech Info Library Article Number:10855