



Tech Info Library

Centris 610 & 650, Quadra 800: Port Pinouts (7/94)

Revised: 7/28/94
Security: Everyone

Centris 610 & 650, Quadra 800: Port Pinouts (7/94)

Article Created: 9 February 1993
Article Reviewed/Updated: 28 July 1994

TOPIC -----

What are the port pinouts on the Macintosh Centris 610, Macintosh Centris 650, and Macintosh Quadra 800?

The information in this article relative to the Centris 610 and Centris 650 is also relevant to the Quadra 610 and Quadra 650.

DISCUSSION -----

The ports supplied with the Centris 610, Centris 650, and Quadra 800 are similar to those supplied with previous Macintosh models. (Note that Ethernet is an option on the Centris 610 and Centris 650.

Video out port Pinouts

1 Red Video Ground
2 Red Video
3 Composite Sync.
4 Monitor ID, Bit 1
5 Green Video
6 Green Video Ground
7 Monitor ID, Bit 2
8 No Connection
9 Blue Video
10 Monitor ID, Bit 3
11 CSYNC and VSYNC Ground
12 Vertical Sync.
13 Blue Ground
14 HSYNC Ground
15 Horizontal Sync.
Shell Chassis Ground

Serial ports (printer and modem)

- 1 Handshake Output DTR
- 2 Handshake Input CTS
- 3 Transmit Data (inverted)
- 4 Ground
- 5 Receive Data (inverted)
- 6 Transmit Data
- 7 No Connection
- 8 Receive Data

External SCSI port

- 1 Request
- 2 Message
- 3 Input/Output
- 4 SCSI bus reset
- 5 Acknowledge
- 6 Busy
- 7 Ground
- 8 Data bit 0
- 9 Ground
- 10 Data bit 3
- 11 Data bit 5
- 12 Data bit 6
- 13 Data bit 7
- 14 Ground
- 15 Command/Data
- 16 Ground
- 17 Attention
- 18 Ground
- 19 Select
- 20 Data parity
- 21 Data bit 1
- 22 Data bit 2
- 23 Data bit 4
- 24 Ground
- 25 Terminator power

ADB ports

- 1 ADB Data
- 2 No Connection - reserved
- 3 +5 volts
- 4 Ground

Ethernet port (Standard on Quadra 800, optional on Centris 610 & Centris 650.)

- 1 No Connection

2	Data Rcv A (RD-A)
3	Data Rcv B (RD-B)
4	Voltage Return (RTN)*
5	Control In A (CI-A)
6	Control In B (CI-B)
7	+5V @ £375 mA*
8	+5V @ £375 mA*
9	Transmit Data A (TD-A)
10	Transmit Data B (TD-B)
11	Voltage Return (RTN)*
12	Reserved (RSV)
13	Reserved (RSV)
14	No Connection
Shld	Shield Ground (GND)

Sound out port

- Sleeve Ground
- Ring Right .75 volt peak-to-peak audio signal right channel
- Ring Left .75 volt peak-to-peak audio signal left channel

Microphone port

- Sleeve Ground
- Ring +8 volts
- Tip Input

Article Change History:

28 Jul 1994 - Added reference to Quadra 610 and 650 to aid in searching.

Support Information Services

Copyright 1993-94, Apple Computer, Inc.

Tech Info Library Article Number:11350