

LaserWriter IIg: Troubleshooting Macintosh and IBM Connections

Revised:	
Security:	Everyone
LaserWriter II	g: Troubleshooting Macintosh and IBM Connections
=========	
Article Created	1: 4 March 1993
TOPIC	
Here is a basic outline to use when troubleshooting a LaserWriter IIg when connected to both a Macintosh and an IBM. If the configuration is IBM only, you may ignore the "Verify Connection to the Macintosh" section.	
oning, you may	sincre the verry connection to the matricosh section.

Verify Connection to the Macintosh

1) Hook up the printer to the Macintosh using two known good LocalTalk boxes and cable.

DISCUSSION -----

- 2) Set the select switch to 0 and turn on the printer.
- 3) In the Chooser, select the printer (If you can't see the printer, you have a hardware problem).
- 4) Try printing a window from the desktop.

If this works, the printer is OK.

Verify IBM Connection

- 1) Use a Null-Modem Cable that connects from the IBM to the IIg.
- 2) Leave the connect switch set to 1, this will set up the DB-25 Serial port to 9600 Baud, HP Emulation.
- 3) Issue the proper Mode commands:

MODE COM*:96,n,8,1,p (Where * is the number of the COMM PORT.)

..TIL11783-LaserWriter_IIg-Troubleshooting_Macintosh_and_IBM_Connections.pdf

```
MODE LPT1:=COM*
```

4) From DOS, not from Windows, perform the following:

Type CTRL-P (This will direct further output to the LPT device.)

Type DIR followed by a RETURN.

Type CTRL-L (This sends a form feed command to eject the page.)

Type CTRL-P (This will redirect the output to the screen.)

You should see the light of the LaserWriter IIg blinking, and then it should produce a printout of the directory of the computer.

If you don't get output at this point, you have a hardware failure. This can be either in the Printer, Cable or Computer.

If the printer does produce a printout, but you can't get the output to work with Windows, then you have a software configuration issue.

Copyright 1993, Apple Computer, Inc.

Tech Info Library Article Number:11783