

## Tech Info Library

## **HyperCard: Handler to Select Multiple Objects (7/92)**

Revised: 12/8/93 Security: Everyone

HyperCard: Handler to Select Multiple Objects (7/92)

\_\_\_\_\_\_

Article Created: 11 January 1991

Article Reviewed/Updated: 23 July 1992

TOPIC -----

This handler allows you to select multiple parts (buttons and fields) by clicking on them. After you've selected them, you can perform operations on all of them using alignParts, deleteParts, offsetParts, and pasteParts.

This article is constrained to a shorter line length than HyperCard scripts can have; you'll have to make adjustments.

DISCUSSION -----

```
on selectParts
```

- -- Group selection: click on parts
- -- Set card script to catch mouseDown and eat mouseUp

global saveCardScript,selectedParts,selectedPartsCard
put empty into selectedParts
put long name of this card into selectedPartsCard
put script of this card into saveCardScript
choose browse tool
put "Click on the parts you wish to select. Press enter to stop."

```
-- write a script
```

put "on mouseDown" & return into scriptVar

put " global selectedParts" & return after scriptVar

put " put the shiftKey is down into deselectFlag" & return after scriptVar

put " if " & quote & "button" & quote & " is not in the target and " & quote

& "field" & quote & " is not in the target" & return after scriptVar

put " then put " & quote & "There is no part there." & quote & return after scriptVar

put " else" & return after scriptVar

put " get the target" & return after scriptVar

put " if " & quote & "id" & quote & " is not word 3 of it" & return after

```
scriptVar
 put "
         then put " & quote & "id " & quote & " & id of the target into last
 word of it" & return after scriptVar
 put " if deselectFlag then" & return after scriptVar
 put "
            if it is not in selectedParts" & return after scriptVar
 put "
            then put the target & " & quote & " is not selected." & quote &
 return after scriptVar
            else" & return after scriptVar
 put "
 put "
             put offset(it & return, selectedParts) into startChar" & return
 after scriptVar
              delete char startChar to startChar + length(it) of
 selectedParts" & return after scriptVar
             put the target & " & quote & " is now deselected." & quote &
 return after scriptVar
            end if" & return after scriptVar
 put " else" & return after scriptVar
 put "
           if it is in selectedParts" & return after scriptVar
 put "
           then put the target & " & quote & " is already selected." & quote
 & return after scriptVar
 put "
          else" & return after scriptVar
 put "
              put it & return after selectedParts" & return after scriptVar
             put the target & " & quote & " is now selected." & quote &
 return after scriptVar
 put " end if" & return after scriptVar
 put " end if" & return after scriptVar
 put " end if" & return after scriptVar
 put " exit to HyperCard" & return after scriptVar
 put "end mouseDown" & return after scriptVar
 put return after scriptVar
 put "on doneSelecting" & return after scriptVar
 put " global saveCardScript,selectedParts" & return after scriptVar
 put " set script of this card to saveCardScript" & return after scriptVar
 put " put the number of lines in selectedParts & " & quote & " parts
 selected" & quote & return after scriptVar
 put "end doneSelecting" & return after scriptVar
 put return after scriptVar
 put "on closeCard" & return after scriptVar
 put " doneSelecting" & return after scriptVar
 put "end closeCard" & return after scriptVar
 put return after scriptVar
 put "on enterKey" & return after scriptVar
 put " doneSelecting" & return after scriptVar
 put "end enterKey" & return after scriptVar
 set script of this card to scriptVar
end selectParts
This article is adapted from the Claris Tech Info database.
Copyright 1993, Apple Computer, Inc.
```

Tech Info Library Article Number:14178