



Tech Info Library

Apple Color StyleWriter Pro: Specifications (7/95)

Revised: 7/14/95
Security: Everyone

Apple Color StyleWriter Pro: Specifications (7/95)

=====

Article Created: 16 February 1994
Article Reviewed/Updated: 14 July 1995

TOPIC -----

This article gives the technical specifications for the Apple Color StyleWriter Pro printer.

DISCUSSION -----

Print Method

- Thermal ink jet

Print Quality

- 360 dpi in normal and best mode
- 180 dpi in draft mode

Interface

- High-speed serial (RS-422)

Speed

- Up to 2 pages per minute for monochrome
- Up to 0.5 page per minutes for color
- Actual speed depends on the documents printed and the Macintosh used

Fonts Supported

- 64 TrueType fonts: ITC Avant Garde, ITC Bookman, Chicago, Courier, Delphian, ITC Garamond Narrow, Geneva, Helvetica, Helvetica Black, Helvetica Compressed, Helvetica Narrow, ITC Lubalin Graph, Lucida Bright, ITC Machine, Monaco, Nadianne, New Century Schoolbook, New York, Old English Text, Onyx, Oxford, Palatino, Swing, Symbol, Times, ITC Zapf Chancery, ITC Zapf

Dingbats, and Zeal

Ink Cartridges

- Separate cartridges for cyan, magenta, yellow, and black
- 315 pages at 5% page coverage per color

Print Materials

- 16 to 24 lb. (60 to 90 g/m²) bond or copier paper
- Paper: U.S. letter, U.S. legal, A4, and envelopes (#10 business, monarch, and other sizes)
- Most letterhead and colored stock, labels, and envelopes
- For superior graphics and imaging results, Apple recommends Apple premium coated paper and Apple back-print media
- For fast dry time and vibrant colors, Apple recommends Apple color ink-jet transparencies

Paper Capacity

- Multipurpose tray that accommodates up to 100 sheets of paper or 15 envelopes

Printable Surface

- Maximum printable line: 8.0 in (20.3 cm)
- Minimum margins: 0.25 in. (.64 cm)

Size and Weight

- Height: 7.2 in. (18.3 cm)
- Width: 16.5 in. (41.9 cm)
- Depth: 10.1 in. (25.7 cm)
- Weight: 11 lb. (5.0 kg)

Power Consumption

- Operating mode: 28 W (maximum)

Operating Environment

- Temperature: 59° F to 86° F (15° C to 30° C)
- Humidity: 10% to 80% noncondensing

Power Requirements

- U.S./Japan: 120 V, 60 Hz, 1 amp
- Europe/Australia: 220 to 240 V, 50 Hz, 0.5 amp

System Requirements

- Any Apple Macintosh personal computer that supports Color QuickDraw and has 4MB of RAM and a hard disk drive. Color QuickDraw first shipped with the

..TIL14658-Apple_Color_StyleWriter_Pro-Specifications_7-95.pdf

Macintosh II, and is in every Macintosh II class computer, which includes the SE/30. This EXCLUDES the Plus, Classic, SE, Macintosh Portable, and the PowerBook 100 (they will not print in color).

- System software version 7.0 or later

Article Change History:

14 Jul 1995 - Added PowerBook 100 and Portable to list of unsupported computers

15 Jun 1994 - Added that only machines that support Color QuickDraw will print in color.

Support Information Services

Copyright 1994-1995, Apple Computer, Inc.

Tech Info Library Article Number:14658