



Tech Info Library

AppleDesign Powered Speakers II: Specifications (8/96)

Revised: 8/2/96
Security: Everyone

AppleDesign Powered Speakers II: Specifications (8/96)

=====

Article Created: 25 October 1994
Article Reviewed/Updated: 2 August 1996

TOPIC -----

This article contains the technical specifications of the AppleDesign Powered Speakers II.

DISCUSSION -----

Speaker Type

- Full-range, tuned-port, bass-reflex system

Output

- Maximum sound-pressure level (SPL) 90 dB at 0.5 m at 200 Hz
- Frequency Range: 150 Hz to 20 kHz
- Power 14 W

Maximum Input Voltage

- 2 volts peak-to-peak

Interfaces

- One stereo computer-sound input port
- One stereo CD/audio input port
- One stereo headphone output port

Control

- Volume on front panel

Power Supply Output

- 12 volts DC

Electrical Requirements

- Line voltage: 100 to 240 volts, depending on the power-supply module
- Frequency: 50 or 60 Hz
- Power: 24 W (maximum)

Size and Weight

- Height: 6.8 in. (175 mm)
- Width: 4.13 in. (107 mm)
- Depth: 3.94 in. (101 mm)
- Weight: 1.34 lb. (612 g)

System Requirements

- Any Apple Macintosh, Macintosh Performa, PowerBook, Power Macintosh, or Windows-based personal computer; CD or cassette player; or television that supports sound output.

Ordering Information

M3261LL/A

- Main (powered) speaker with amplifier and satellite speaker in slate color
- Power-supply module (120-volt input)
- Computer cable (with 3.5-mm miniplugs)
- CD stereo cable (3.5-mm miniplug to dual RCA jacks)
- Attached, insulated, dual-strand speaker-to-speaker cable with miniplug connectors
- User's guide
- Limited warranty

M2668LL/A

- Identical to M3261LL/A, but platinum in color to match Macintosh computers

Article Change History:

02 Aug 1996 - Article Reviewed.

03 Jan 1995 - Article reviewed.

Copyright 1994-96, Apple Computer, Inc

Tech Info Library Article Number:16600