

## Tech Info Library

## Apple Hard Drives: Termination Requirements (10/94)

Revised: 10/28/94 Security: Everyone

Apple Hard Drives: Termination Requirements (10/94)

\_\_\_\_\_\_

Article Created: 28 October 1994

TOPIC -----

Hard drives or DAT drives may need to have the termination resistors removed or made inoperative on certain configurations of multiple drive systems or WorkGroup Servers. Below is a brief description of termination requirements for the different systems or WorkGroup Servers.

DISCUSSION -----

Computer Model Termination Requirement

Quadra/Centris 660 AV Hard Drive needs termination Quadra/Centris 610

Power Macintosh 6100/60 Workgroup Server 60 Workgroup Server 6150

Power Macintosh 7100/66

Macintosh IIvx, IIvi Hard Drive needs termination Quadra/Centris 650

Quadra 800/840 AV Last drive in line needs termination.

Remove termination from all other drives

installed, including DAT.

Power Macintosh 8100/80 Has two internal cables: Workgroup Server 8150 1) Internal/external cab

1) Internal/external cable requires that
 all drives have no termination. Remove
 termination from all internal drives
 (termination is on cable)

2) The internal channel cable (max 1 drive only) requires termination.

Quadra 900 Remove termination from all internal

## ..TIL16628-Apple\_Hard\_Drives-Termination\_Requirements\_10-94\_(TA32808).pdf

Quadra 950 Workgroup Server 95 Workgroup Server 9150 drives (termination is on cable).

Support Information Services

Copyright 1994, Apple Computer, Inc.

Tech Info Library Article Number:16628