



Tech Info Library

StyleWriter II: Special Communication Specifications (4/96)

Revised: 4/29/96
Security: Everyone

StyleWriter II: Special Communication Specifications (4/96)

Article Created: 26 April 1996

TOPIC -----

I am trying to use a special device with the StyleWriter II printer. However, I need some information I couldn't find in the StyleWriter II printer manual. I need the data bits, stop bit, baud rate, and parity.

DISCUSSION -----

The information you need is listed in the table below. However, the StyleWriter II is a QuickDraw printer. Unlike many MS-DOS/Windows printers, QuickDraw printers require special drivers, and do not have a built-in character set or support emulation modes such as Epson, or Hewlett-Packard (HP).

In addition to the information in the table, you will need to write a custom QuickDraw driver if the StyleWriter II is used on any computer other than a Macintosh. Writing a custom driver is NOT an easy task, and requires knowledge of both programming and printer command sequences.

StyleWriter II Communication Specifications

+=====+		
Data Type	Data Rate	
+=====+		
Start Bits	1	
+-----+		
Data Bits	8	
+-----+		
Stop Bits	1	
+-----+		
Baud Rate	57.6 Kilobit per seond (Default)	
	230.4 Kbps (software selectable	
+-----+		

Parity	None	
+-----+	+-----+	+-----+

DIN-8 Connector (RS-422)
=====

+=====+	+=====+	+=====+
Pin #	Signal	Description
+=====+	+=====+	+=====+
1	NC	No connection
+-----+	+-----+	+-----+
2	NC	No connection
+-----+	+-----+	+-----+
3	TxD-	Transmit Data, negative
+-----+	+-----+	+-----+
4	SG	Signal Ground
+-----+	+-----+	+-----+
5	RxD-	Receive Data, negative
+-----+	+-----+	+-----+
6	TxD+	Transmit Data, positive
+-----+	+-----+	+-----+
7	PWR	Optional interface power
+-----+	+-----+	+-----+
8	RxD+	Receive Data, positive
+=====+	+=====+	+=====+

Copyright 1996, Apple Computer, Inc.

Tech Info Library Article Number:19674